

Octa-Liner sliding gate

Your property and access, our challenge

SLIDING GATES



Octa-Liner: excellent price and performance

The Octa-Liner: for years an established name in the B&G Entrance Control sliding gates range. This steel gate is very suitable for opening widths of 4 to 8 meters. De Octa-Liner is crash-resistant, maintenance-friendly and attractively priced.

Fits any fencing

The Octa-Liner fits any fencing. B&G supplies the sliding gate in Barricade, Rondissade and Stockade versions and

with welded mesh filling. The gate is available in all RAL-colours.

Applications

- industrial sites
- business parks



Security starts outside



Octa-Liner

TECHNICAL SPECIFICATIONS

Octa-Liner type single	300	400	500	600	700	800
Clear opening	3000	4000	5000	6000	7000	8000
Space required	7350	9700	12500	14400	16450	18500
Octa-Liner type double	600	800	1000	1200	1400	1600
Clear opening	6000	8000	10000	12000	14000	16000
Space required	14420	19120	24720	28250	32620	36720
Gate heights	1000	1250	1500	1800	2000	2500

Dimensions in ca. mm.

Version

Construction

Gate frame

- lower beam: steel, round 152.4 mm
- gate frame: steel case 60x60 mm.
- diagonal tension cable: all gates except for type 300
- double diagonal tension cable: with types 600, 700 and 800, 1250 mm. and up

Beware: types 600, 700, 800 not available in height 1000 mm.

Slam & guiding posts

- 1st guiding post: 120x80 mm / 80x60 mm
- 2nd guiding post (road wheel block): 80x60 mm
- slam post: 80x80 mm
- finish: black plastic cover

Infill

- **Barricade:** round 30 mm, centre-to-centre distance 150 mm. Gates of a 1500 mm height or up are provided with a pointed comb (35 mm high, sharp points).
- **Stockade:** square 25x25 mm, centre-to-centre distance 150 mm, bevelled bar tops with gates of a 1500 mm height or up, bars are guided through the lower- and top beam.
- **Rondissade:** round 30 mm, centre-to-centre distance 150 mm, bevelled bar tops with gates of a 1500 mm height or up, bars are guided through the lower- and top beam.

Locking mechanism

- lock with dead bolt

Surface treatment

- hot-dip galvanized
- hot-dip galvanized and powder coated according to the Duplex-system

Standard colours

- RAL 6009 (pine green)
 - RAL 6005 (moss green)
 - RAL 9005 (black)
- Other RAL-colours are available upon request.

Drive

- GT (approx. 20 cm/s)
- BT (approx. 30 cm/s)

Assembly

- fix slam & guiding posts in a poured concrete foundation

Industrieweg 187a
NL-5683 CC Best
PO Box 66
NL-5680 AB Best

Tel.: +31 499 363 666
Fax: +31 499 399 945
info@bgfencing.com



www.bgfencing.com



GARDA
SIKRING